



SkimOIL, Inc
103 W. Weaver Street
Carrboro, NC 27510
(314) 579-9755
Fax: (314) 558-9253
www.skimoil.com

Marine and Industrial Solutions Since 1995

EMAIL: contact@skimoil.com

Chemical Transfer Hose UHMWPE Tube



APPLICATION:

Verstile, premium quality, light weight, heavy duty flexible chemical transfer hose. Where a single hose is required to transfer a wide range of solvents, acids, corrosive solutions and chemicals from storage tanks, bulk plants, trucks and tank cars.

CONSTRUCTION:

UHMWPE Tube, reinforced with multiple layers of textile and helix wire, weather and abrasion resistant EPDM cover.

LENGTHS:

Up to a 100 Feet

COUPLINGS:

Male and Female Shank Couplings, Combination Nipples and Quick Couplings

SIZE ID	APPROX. OD	MAXIMUM WORKING PRESSURE	VACUUM	MINIMUM BEND RADIUS	APPROX. WEIGHT/FT
INCH	INCH	PSI	IN/HG	INCH	LBS
3/4"	1.19"	150	28	3.50	0.52
1"	1.47"	150	28	4.00	0.53
1-1/4"	1.78"	150	28	4.00	0.75
1-1/2"	2.08"	150	28	4.00	.96
2"	2.58"	150	28	6.00	1.30
2-1/2"	3.13"	150	28	8.00	1.77
3"	3.66"	150	28	9.00	2.09
4"	4.70"	150	28	12.00	2.92