



SkimOIL, Inc
103 W. Weaver Street
Carrboro, NC 27510
(314) 579-9755
Fax: (314) 558-9253
www.skimoil.com

Marine and Industrial Solutions Since 1995

EMAIL: contact@skimoil.com

Petroleum, Tanker, Vac-Truck Transfer Hose



Application:

Used to transfer Gasoline, Fuel Oils, Paraffin and other Petroleum Products from storage tanks, Bulk Tanks, Trucks and Tank Cars where aromatic content does not exceed 40%. For both suction and discharge service. Maximum Temperature 200° F.

Construction:

Oil-Resisting Nitrile Tube, Oil and Abrasion-Resisting Cover. Reinforced with Wire Helix(s) and multiple layers of Textile.

Lengths:

Up to a 100 feet.

Couplings:

Male and Female Shank Couplings, Combination Nipples, and Quick Couplings.

Size ID	Approx OD.	Maximum Working Pressure	Vacuum	Minimum Bend Radius	Approx. Weight/FT
Inch	Inch	PSI	In/HG	Inch	Lbs
3/4"	1.14	150	28	3.00	0.52
1"	1.38	150	28	3.00	0.53
1-1/4"	1.66	150	28	3.50	0.75
1-1/2"	2.00	150	28	4.50	.80
2"	2.47	150	28	6.00	1.00
2-1/2"	3.06	150	28	7.50	1.50
3"	3.56	150	28	9.00	1.70
4"	4.63	150	28	12.00	2.50