



SkimOIL, Inc
 103 W. Weaver Street
 Carrboro, NC 27510
 (314) 579-9755
 Fax: (314) 558-9253
 www.skimoil.com
 EMAIL: contact@skimoil.com

Marine and Industrial Solutions Since 1995

Steam Hose



Application: Used for Cleaning, Heating, De-Icing, Fire Fighting and Emergency Steam Service at Chemical Plants, Refineries, Steel Mills, Marine Installations and Throughout Industry.

Couplings: "Boss" Type Interlocking Male or Female Couplings and Bolted Clamps.

150 PSI WORKING PRESSURE

RECOMMENDED FOR STEM CLEANING SERVICE ONLY. Heat and Oil Resisting Tube and Cover, Reinforced with Braid of High Tensile Wire for temperatures to 366°F. Tube is resistant to detergents commonly used.

SIZE ID	APPROX OD.	MAXIMUM WORKING PRESSURE	APPROX. WEIGHT/FT
INCH	INCH	PSI	LBS
3/8"	25/32"	150	0.30
1/2"	29/32"	150	0.32

250 PSI WORKING PRESSURE

Heat Resisting EPDM Rubber Tube and EPDM cover reinforced with cords of High Tensile Wire. Can be used for temperatures up to 450°F. NOT Recommended for use with super saturated steam or for steam cleaning service.

SIZE ID	APPROX OD.	MAXIMUM WORKING PRESSURE	APPROX. WEIGHT/FT
INCH	INCH	PSI	LBS
1/2"	1-1/32"	250	0.38
3/4"	1-1/4"	250	.052
1"	1-7/16"	250	0.62
1-1/4"	1-13/16"	250	0.87
1-1/2"	2-1/8"	250	1.10
2"	2-5/8"	250	1.51